

Water Chiller - efficient, compact design

HYFRA eChilly series

- Plug and Play: easy to install
- Compact design with micro-channel technology
- Energy efficient: less power consumption
- Low noise: for in-room application
- Protects the environment: 60% less refrigerant



1  6 kW

HYFRA eChilly - Plug and Play water chiller

TECHNICAL DATA

		eChilly 1	eChilly 2	eChilly 3	eChilly 4	eChilly 5	eChilly 4-3	eChilly 5-3	eChilly 6-3	
ambient temp. °C	water °C	cooling capacity Watt								
		10	920	2100	2740	3750	2740	3750	4690	
32	15	775	1290	2450	3565	4525	3565	4525	5660	
	20	1025	1655	2810	4395	5480	4395	5480	6800	
	10	345	675	1645	2240	3450	2240	3450	4310	
37	15	615	1050	2060	3080	4395	3080	4395	5490	
	20	890	1425	2475	3920	5340	3920	5340	6680	
	10	205	450	1390	1740	3045	1740	3045	3810	
42	15	480	765	1810	2580	3870	2580	3870	4840	
	20	755	1085	2230	3420	4690	3420	4690	5860	
	10	65	67	67	68	68	68	68	68	
sound pressure level *(1)	dB(A)	65	67	67	68	68	68	68	68	
power consumption max. *(2)	kW	0,9	1,5	1,9	2,3	2,7	2,2	3,0	3,7	
current consumption max. *(2)	A	4,6	7,6	10,0	11,0	11,3	4,4	5,7	7,0	
voltage supply		230V 1Ph					400V 3Ph			
air flow rate max.	m³/h	800	1290	1290	1350	1350	1350	1350	2390	
tank capacity	l	6	20	20	26	26	26	26	26	
water pressure	bar	2,2	3,6	2,9	3,1	3,3	3,1	3,3	3,3	
nominal water flow	l/min	2,3	4,3	7,2	10	12,9	10	12,9	12,9	
water connections	inch	1/2 (6 or 9mm also available)								
width	mm	560	710			760				
depth	mm	475	545			635				
height	mm	355	450			500				
net weight (approx.)	kg	49	55	65	81	90	81	90	90	

*(1) in 1 meter distance in free field (tolerance +/- 1dB(A))

Technical data temporarily

*(2) at 42°C ambient temp. and 20°C water temp.

eChilly 1 - 3 also available without digital thermostat, please ask for description and options

TECHNICAL DESCRIPTION:

- Stainless steel cover
- Metal mesh air filter
- Micro-channel condenser, pure aluminum
- Water level indication
- Digital thermostat with hysteresis of +/- 1K
- Common alarm indication
- Bypass for pump protection
- Common alarm
- Ambient temperature < 42° C

OPTIONS, some:

- Alarm water loss
- Manometer in water circuit
- Flow control switch
- 2 x water IN/OUT
- Stronger pumps available
- Automatic water refill
- Several standard power supplies available
- Harting-plug connectors
- Single marking
- Wheel version available
- Water cooled condenser
- Winter start option; outside use kit
- More accurate temperature hysteresis